




**BRIDGEHILL®**  
WE SIMPLY BLOCK FIRE

FIRST RESPONDER

# PALLET TRUCK/FORKLIFT STANDARD



## Product information

- Controls fire in forklifts within seconds
- The most efficient solution for isolating fire in forklifts, even electric battery powered
- Immediately isolates toxic gases and smoke, protecting civilians from carcinogen exposure
- Protecting the goods and buildings from fire, reducing down time
- Delivered in a smartbag
- EN 13501-1: Reaction to fire classification A1
- EN ISO 1716: Determination of the gross heat of combustion
- EN ISO 1182: Non-combustibility test

## Ideal for:

Warehouses – Ports – Factories –  
Manufacturing companies and other places  
where it is critical to control fire quickly



For instruction videos  
scan QR code



## Size/Weight:

**Pallet truck:** ± 5 × 5 m  
± 15 kg


**Forklift standard:** ± 7 × 7 m  
± 30 kg

## How to use

Handled by: 

1. Place the fire blanket on the ground in front or behind the forklift and roll it out.
2. Two people should grab each their handle and safely pull the fire blanket over the forklift in one continuous movement.
3. On forklifts with a tall mast, cover the cabin not the mast. Please see illustration.
4. Make sure the fire blanket is tight all the way to the ground and leave the fire blanket on for minimum 20 minutes. Wait for firefighters to assess the situation further..

**Pallet truck:** ± 5 × 5 m



**Forklift standard:** ± 7 × 7 m



**ALWAYS CALL THE  
FIRE DEPARTMENT!**

**Fire in electric forklifts:** In many cases you might hear a strong fuzzing sound, which indicates a thermal runaway. We recommend to leave the fire blanket on until the vehicle has been transported to a safe place and assessed by professionals. Remember that a battery might reignite at any time.



**BRIDGEHILL®**  
WE SIMPLY BLOCK FIRE

TECHNICAL SHEET

# PALLET TRUCK/FORKLIFT STANDARD

## FIRST RESPONDER

<b>SKU:</b>	Pallet Truck: 211227 Forklift Standard: 201252
<b>Size/Weight:</b>	Pallet Truck: ± 5 × 5 m (25 m <sup>2</sup> ) / ± 15 kg Forklift Standard: ± 7 × 7 m (49 m <sup>2</sup> ) / ± 30 kg
<b>Core material:</b>	380 gsm pyroxene
<b>Coating:</b>	± 120 silicone polymer (flames may occur during first time use). In fires with high levels of conduction heat, flames may appear from the coating of the fire blanket. This will not alter the performance of the fire blanket
<b>Main usage:</b>	<ul style="list-style-type: none"> <li>• Fossil fuel forklifts</li> <li>• Electric forklifts (isolating the fire in the battery)</li> </ul>
<b>Smartbag:</b>	Airtight bag. Smartbag care and maintenance: Use silicon grease on the zipper to keep the bag airtight and smell free.

### Technical specification:

Core Fabric			Unit	Tolerance
Yarn	Warp	300	Tex Tex	± 5%
	Weft	165		
Yarn count	Warp	8.0	Ends/cm Ends/cm	± 5%
	Weft	8.0		
Tensile strength (typical)	Warp	3200	N/50mm N/50mm	≥
	Weft	2500		
Thickness	–	0.40	Mm	± 5%
Weave pattern	–	Plain	–	–
Service temperature on core fabric	Short term ± 1600 °C Long term ± 800 °C			

## WARNING:

Avoid inhaling smoke from the burning object. Do not put yourself at unnecessary risk, call the fire department!

In fires with high levels of conduction heat, flames may appear from the coating of the blanket. This will not alter the purpose of the blanket.