






Bubblemat Connect

Interlocking tiles with high anti-fatigue properties



- Durable anti-fatigue matting system.
- Raised bubbled surface to stimulate blood circulation and reduction of fatigue.
- Interlocking system provides flexibility in the type of shape that can be created.
- Soft but sturdy rubber material offers protection from adverse effects from cold, hard concrete floors.
- Rubber is naturally slip resistant.



Parts

Part Number	Size	Colour	Weight (kg)
BF010709	50 cm x 50 cm	Black/Yellow	2.15

Technical Specifications

Material	Natural rubber
Recycled Material	43% recycled content

Part Number	Size	Colour	Weight (kg)
BF010708	50 cm x 50 cm	Black/Yellow	2.15
BF010009	50 cm x 50 cm	Black	2.15
BF010008	50 cm x 50 cm	Black	2.15
BF010007	50 cm x 50 cm	Black	2.15

Content %	
Surface Finish	Bubble
Product Height	13.5 mm
Product Weight	5,75 kg
Min. Operating Temperature	-30°C
Max. Operating Temperature	+50°C
Resistance to Chemicals	Not resistant to fat and mineral oil
Environmental Resistance	Suitable for dry indoor environments
UV Resistance	Yes
Installation Method	Loose lay interlocking mats
Cleaning Method	Use a high pressure hose (not exceeding 60psi) to remove the dirt and debris on the mats. For best results use a mild detergent (pH 4.0-9.0) to clean the mats. Do not use steam or degreasers or caustic chemicals. Do not mechanically scrub the mats.
Tensile Strength	3 MPa
Elongation	250%
Manufacturing process	Compression moulding

Get in touch | To order FREE samples or arrange a site visit please call +44 (0)1788 228 555 or email sales@coba.com

www.coba.com