





A durable anti-slip mat ideal for areas prone to oil or chemical spillage













- A solid surface mat designed to reduce slips in oily or greasy conditions.
- · Raised surface pattern provides extra underfoot grip.
- Recessed pattern creates drainage channels to capture liquids.
- Makes standing more comfortable in a wide range of workplace environments.
- Resilient to degradation in oily, greasy and chemical prone areas for a longer lifespan.
- Single mat design makes it a quick and simple solution to reduce slip accidents.
- Bevelled edges as standard to reduce the risk of trips.
- Slip tested to DIN 51130.















Parts

Part Number	Size	Colour	Weight (kg)
CS010004	1.15 m x 1.75 m	Black	8.5
CS010003	0.85 m x 3 m	Black	10.5
CS010002	0.85 m x 1.5 m	Black	6
CS010001	0.85 m x 0.75 m	Black	5.8

Technical Specifications

Material	NBR
Surface Finish	Raised rectangular cleats
Product Height	6 mm
Product Weight	4.2 kg / m ²
Min. Operating	-20°C

Temperature	
Max. Operating Temperature	+70°C
Resistance to Chemicals	Resistant to many chemicals, alkalis, detergents, oils, machine coolants and general industrial coolants. Rubber may swell in polar solvents.
Environmental Resistance	Suitable for wet and dry environments, indoors or outdoors
UV Resistance	Yes
Typical Applications	Food manufacturing, General industrial
Installation Method	Loose Lay
Cleaning Method	0.75 m x 0.85 m can be washed in standard domestic washing machines. All other sizes can be laundered in commercial washing machines or hosed down with a high pressure washer.
Slip Tested to	DIN 51130 - R10

Additional Information



COBAscrape DIN 51130 Ramp Slip Test

Get in touch | To order FREE samples or arrange a site visit please call +44 (0)1788 228 555 or email sales@coba.com

www.coba.com