



COBAdeluxe

Fatigue relief for heavy-duty workstations









- Creates a safe and very comfortable standing surface.
- Its thickness makes it a durable mat that can withstand impact.
- Quickly cover large areas if used as a connecting system.
- Made from hardwearing rubber providing longevity.
- · Excellent slip resistance in wet areas.
- Open drainage holes for spilt liquids make it ideal for wet workplaces.
- Available as a single mat or can be linked together with connectors for larger areas.
- Slip tested to DIN 51130.













Parts

Part Number	Size	Colour	Weight (kg)
DM010003	70 mm x 70 mm x 17 mm	Black	0.3
P240-L1092-C09	1074 mm x 50 mm	Black	0.65
P240-L1093-C09	1565 mm x 50 mm	Black	0.95
DM010002	1 m x 1.5 m	Black	16.4

Technical Specifications

Material	Natural rubber
Recycled Material Content %	43
Surface Finish	Circular pattern construction for extra grip and holes to allow drainage
Product Height	18.5 mm
Product Weight	15 kg
Hole Size	13 mm, 24 mm
Min. Operating Temperature	-20°C
Max. Operating Temperature	+50°C
Resistance to Chemicals	Not resistant to fat and mineral oil

Environmental Resistance	Suitable for indoor and outdoor environments
UV Resistance	Yes
Typical Applications	General industrial
Installation Method	Loose Lay
Cleaning Method	Wash down with hose or pressure wash
Tensile Strength	3 MPa
Elongation	250%
Application Temperature	-30°C to 50°C
Slip Tested to	DIN 51130 - R10
Manufacturing process	Compression moulding

Additional Information



COBA Deluxe Ramp Slip Test DIN 51130

Get in touch | To order FREE samples or arrange a site visit please call +44 (0)1788 228 555 or email sales@coba.com

www.coba.com