

DataSheet

The home of innovation and elite performing PFAS-free fire extinguishers in the UK, CommanderEDGE boasts a number of reliable and extensively tested fire extinguishers. The range is fully Kitemarked by BSI and is the choice of the professional with its mix of performance, quality and value.

WATER FIRE EXTINGUISHERS

Ideal for Class A fire risk areas (those featuring combustible materials), water-based fire extinguishers remain a popular choice for many businesses.

The CommanderEDGE enviroWater contains a PFAS-free additive that boasts rapid knock-down capabilities in a compact, portable unit; pointed at the base of the fire, this extinguisher releases water to cool the fuel, ensuring it burns at a slow pace until it's completely extinguished

Technical Specification	FX-FFW-003-CCF	FX-FFW-006-CCF	FX-FFW-009-CCF
Capacity	3 litre	6 litre	9 litre
Fire Rating	13A	27A	43A
Extinguishing Medium	Water + Additive	Water + Additive	Water + Additive
Working Pressure	15 bar @ 20°C	15 bar @ 20°C	15 bar @ 20°C
Temperature Range	0°C to 60°C	0°C to 60°C	0°C to 60°C
Cylinder Material	Steel	Steel	Steel
Pressuring Gas	Nitrogen	Nitrogen	Nitrogen

029 2086 8333

sales@checkfire.co.uk

029 2085 0627

www.CheckFire.co.uk



COMMANDEREDGE

PRODUCT CODE
FX-FFW-003-CCF | FX-FFW-006-CCF |
FX-FFW-009-CCF

PRODUCT GROUP
CommanderEDGE Extinguishers

DIMENSIONS (mm) (height x width x diameter)
FX-FFW-003-CCF: 416 x 233 x 130
FX-FFW-006-CCF: 495 x 285 x 165
FX-FFW-009-CCF: 566 x 305 x 190

WEIGHT FX-FFW-003-CCF: 5.3kg
FX-FFW-006-CCF: 9.3kg
FX-FFW-009-CCF: 14.0kg

- Kitemarked to BS EN3
- MER approved
- UKCA and CE approved
- 35kVa Dielectric test certified
- Plastic base skirt for protection
- Polyethylene internal lining
- Full range of spare parts available
- 5-year warranty

