



Fatigue-Step® Grit Top

Fatigue relief with superior slip resistance



- 'Grit' top surface provides exceptional grip even in oily conditions.
- Extremely robust interlocking tiles for heavy-duty use.
- Open holes allow efficient drainage of spilt liquids.
- Provides high levels of comfort underfoot to relieve fatigue.
- Made from nitrile for excellent resistance to oils and chemicals.
- Slip tested to DIN 51130.
- Optional ramped edging in yellow or black.



Parts

Part Number	Size	Colour	Weight (kg)
SS010001G	0.9 m x 0.9 m	Black	9.95

Technical Specifications

Material	100% Nitrile, including 20% recycled content
Recycled Material Content %	20%
Surface Finish	Carbide bonded to rubber with holes to allow drainage
Product Height	18 mm
Hole Size	22 mm
Min. Operating Temperature	-20°C
Max. Operating Temperature	+130°C

Resistance to Chemicals	NBR offers excellent resistance to oils and chemicals
Environmental Resistance	Suitable for wet and dry environments. Will withstand welding splatter and spillages of other hot materials.
UV Resistance	Yes
Typical Applications	General industrial
Installation Method	Loose lay interlocking tiles
Cleaning Method	Wash with cold water, use vacuum cleaner or use pressure pump to remove dirt
Tensile Strength	2.5 to 4 MPa
Notes	Silicone is used in the production process of the mats and a residue will possibly be left on the mat
Slip Tested to	DIN 51130 - R13

Additional Information



Fatigue Step Grip DIN 51130 Ramp Slip Test

Get in touch | To order FREE samples or arrange a site visit please call +44 (0)1788 228 555 or email sales@coba.com

www.coba.com