

#### Worksafe

If greasy floors are a problem, this is your ideal anti-slip mat!













- Improves comfort during prolonged standing.
- Hardwearing making it suitable for many industrial environments a choice of two colours.
- Blue oil-resistant option is ideal for greasy, oily workstations where slips pose a threat.
- Open holes capture spilt liquids and swarf.
- Effectively reduces slip hazards where spillage is prevalent.
- A complete mat that can be used as immediate safety solution.
- Bevelled edging all round to reduce the risk of trips.
- Slip tested to DIN 51130.
















# Styles Available





Black

#### **Parts**

| Part Number | Size          | Colour | Weight (kg) |
|-------------|---------------|--------|-------------|
| SW020001    | 0.9 m x 1.5 m | Blue   | 14          |
| SW010001    | 0.9 m x 1.5 m | Black  | 14          |

# **Technical Specifications**

| Material                         | Black version 70% recycled content Blue version 40% recycled content                                  |  |
|----------------------------------|---|--|
| Surface Finish                   | Textured surface with holes   |  |
| Product<br>Height                | 16 mm   |  |
| Hole Size                        | 22 mm   |  |
| Min.<br>Operating<br>Temperature | -20°C   |  |
| Max.<br>Operating<br>Temperature | +130°C  |  |
| Resistance to Chemicals          | Natural rubber is resistant to water and most mild acids  |  |
| Environmental<br>Resistance      | Suitable for wet and dry indoor environments  |  |
| UV Resistance                    | Yes   |  |
| Typical<br>Applications          | Welding bays, Machine tool areas where swarf is prevalent   |  |
| Installation<br>Method           | Loose Lay   |  |
| Cleaning<br>Method               | Wash with cold water, use vacuum cleaner or use pressure washer to remove dirt                        |  |
| Tensile<br>Strength              | 3.5 to 4 MPa  |  |
| Notes                            | Silicone is used in the production process of the mats and a residue will possibly be left on the mat |  |
| Slip Tested to                   | DIN 51130 - R10   |  |

### Additional Information

