



## Fatigue-Step® Solid Nitrile

### Impact-Resistant Interlocking Nitrile Tiles



- Tiles link together to provide a very comfortable anti-fatigue surface.
- Simple to press-together connectors for installation on-site.
- Individual tiles can be moved and replaced with ease.
- Fully slip tested – see datasheet for details.
- Made with 100% Nitrile material content for excellent resistance to oils, chemicals and grease.
- Fire tested to BS EN 13501 – see datasheet for details.
- Optional ramped edging in yellow or black.



## Parts

| Part Number | Size          | Colour | Weight (kg) |
|-------------|---------------|--------|-------------|
| ST010001B1  | 0.9 m x 0.9 m | Black  | 10.5        |

## Technical Specifications

|                                |                                            |
|--------------------------------|--------------------------------------------|
| <b>Material</b>                | Nitrile version - 100% NBR                 |
| <b>Resistance to Chemicals</b> | Excellent resistance to oils and chemicals |
| <b>Typical Applications</b>    | General industrial                         |
| <b>Fire Tested to</b>          | B1 version: BS EN 13501-1 Class Bfl - s1   |

## Additional Information



Solid Fatigue Step B1 Fire Test BS EN 13501



Solid Fatigue Step B1 Fire Test EN ISO 9239



Solid Fatigue Step B1 Fire Test EN ISO 11925

Get in touch | To order FREE samples or arrange a site visit please call +44 (0)1788 228 555 or email [sales@coba.com](mailto:sales@coba.com)

[www.coba.com](http://www.coba.com)