



## Fatigue-Step® Solid

Modular anti-fatigue matting for larger areas



- Tiles link together to provide a very comfortable anti-fatigue surface.
- Simple to press-together connectors for installation on-site.
- Compatible with Fatigue-Step Grit tiles.
- Individual tiles can be moved and replaced with ease.
- Manufactured with Natural rubber and 25% nitrile.
- Fully slip tested – see datasheet for details.
- Optional ramped edging in yellow or black.



## Parts

| Part Number | Size          | Colour | Weight (kg) |
|-------------|---------------|--------|-------------|
| ST010001    | 0.9 m x 0.9 m | Black  | 10.5        |

## Technical Specifications

|                            |                                        |
|----------------------------|----------------------------------------|
| Material                   | Standard - Natural rubber with 25% NBR |
| Surface Finish             | Solid textured                         |
| Product Height             | 18 mm                                  |
| Min. Operating Temperature | -20°C                                  |
| Max.                       | +130°C                                 |

|                                 |                                                                                                                                                     |
|---------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Operating Temperature</b>    |                                                                                                                                                     |
| <b>Resistance to Chemicals</b>  | Limited resistance to chemicals and oils                                                                                                            |
| <b>Environmental Resistance</b> | Suitable for wet and dry environments. Will withstand welding splatter and spillages of other hot materials.                                        |
| <b>UV Resistance</b>            | Yes                                                                                                                                                 |
| <b>Typical Applications</b>     | General industrial                                                                                                                                  |
| <b>Installation Method</b>      | Loose lay interlocking tiles                                                                                                                        |
| <b>Cleaning Method</b>          | Use of hard detergents not recommended                                                                                                              |
| <b>Storage and application</b>  | Store at room temperature, free from deformations.                                                                                                  |
| <b>Tensile Strength</b>         | 3.5 to 4 MPa                                                                                                                                        |
| <b>Notes</b>                    | Silicone is used in the production process of the mats and a residue will possibly be left on the mat. This can be washed off using hot soapy water |
| <b>Slip Tested to</b>           | DIN 51130 - R10                                                                                                                                     |

## Additional Information



Installation Guide



Solid Fatigue Step Ramp Slip Test DIN 51130

Get in touch | To order FREE samples or arrange a site visit please call +44 (0)1788 228 555 or email [sales@coba.com](mailto:sales@coba.com)

[www.coba.com](http://www.coba.com)